

MATERIAL SAFETY DATA SHEET

SAFETEC OF AMERICA	May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.		HMIS HAZARD RATING			
	HEALTH	1	0 = INSIGNIFICANT		3 = HIGH	
	FLAMMABILITY	1	1 = SLIGHT		4 = EXTREME	
	REACTIVITY	0	2= MODERATE			
	TRANSPORTATION INFORMATION					
	PROPER SHIPPING NAME		Not Regulated			
	HAZARD CLASS/PKG. GRP.		None/None		REF.	N/A
	IDENTIFICATION NUMBER		None		LABEL	None Required

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

Page 1 of 2

RED Z

MANUFACTURER'S NAME Safetec of America, Inc.	EMERGENCY TELEPHONE NUMBER (24 Hours) (800) 255-3924
ADDRESS (NUMBER, STREET, P.O. BOX) 887 Kensington Ave.	TELEPHONE NUMBER FOR INFORMATION (716) 895-1822
(CITY, STATE AND ZIP CODE) Buffalo, NY 14215	DATE PREPARED September 1, 2010
	SUPERSEDES January 7, 2009

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	ACGIH TLV/TWA/STEL			
			PPM	MG/M ³	PPM	MG/M ³
Superabsorbent polymer, CAS proprietary		>97		5 (PEL)		5 (TLV)
Sodium dichloro-s-triazinetriene	2893-78-9		None Established		None Established	

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
INHALATION: Breathing of dust may cause throat and upper respiratory tract irritation.	Remove to fresh air; seek medical attention if required.
EYES: May cause moderate irritation associated with redness and burning sensation.	Flush eyes with clear running water for a minimum of 15 minutes while holding eyelids open; if irritation persists, seek medical attention.
INGESTION: Ingested material may cause burning of mouth, throat and esophagus, abdominal distress and moderate irritation.	Drink large amounts of water. DO NOT induce vomiting. Seek medical attention.
SKIN: Prolonged or repeated contact may cause skin irritation.	Flush with clear running water for a minimum of 15 minutes; if irritation persists, seek medical attention.
HEALTH HAZARDS (ACUTE AND CHRONIC):	Acute effects are possible irritation and discomfort; chronic exposure to large amounts of this material has not been characterized and the irritating properties of the material make such an exposure highly unlikely.

CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
No additional information						

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Pre-existing skin or breathing disorders may become aggravated through prolonged exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

RED Z

Page 2 of 2

Date: January 7, 2009

SECTION 4 - FIRE FIGHTING MEASURES**FLASH POINT (METHOD USED)**

Not Applicable

FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component)

LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA

Water, water spray, water fog

SPECIAL FIRE FIGHTING PROCEDURES

Use water spray to cool fire-exposed containers and structures. Wear NIOSH/MSHA approved self contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS

Spilled material swells and becomes extremely slippery when wet. Use standard safety precautions for finely divided powders. Thermal decomposition may emit chlorine containing substances.

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES**STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED**

In case of accidental spills, provide adequate ventilation; avoid generating dust. Vacuum (using HEPA filter equipped system) if possible to avoid generating airborne dust. Place spilled material into a clean, dry container for disposal. Do not close disposal containers containing wet or damp material; they should be left open to disperse any chlorine gas that may form.

WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container(s) tightly closed when not in use. Store in cool, dry area. Keep this and other chemicals out of reach of children.

SECTION 6 - EXPOSURE CONTROLS/PERSONAL PROTECTION**RESPIRATORY PROTECTION**

Use NIOSH/MSHA approved or equivalent with high efficiency filter for particulate levels

above 0.05mg/m³**VENTILATION**

LOCAL EXHAUST: Recommended

MECHANICAL (GENERAL): As appropriate

PROTECTIVE GLOVES

Impervious rubber

EYE PROTECTION

Safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Ordinarily, none required.

WORK/HYGIENIC PRACTICES

Practice safe work habits. Use according to label instructions.

SECTION 7 - PHYSICAL/CHEMICAL PROPERTIES**BOILING POINT**

Not Applicable

SPECIFIC GRAVITY (WATER = 1)

43.7 - 51.8 lb./cu.ft.

VAPOR PRESSURE (mm Hg)

Not Applicable

MELTING POINT

>482°F (partial to full decomposition)

VAPOR DENSITY (AIR = 1)

Not Applicable

pH

No data

SOLUBILITY IN WATER

Slight

EVAPORATION RATE (n-BUTYL ACETATE=1)

Not applicable

APPEARANCE AND ODOR

Off-white, granular powder; slight chlorine odor

% VOLATILES (BY WEIGHT)

Not applicable

SECTION 8 - STABILITY AND REACTIVITY**STABILITY**

UNSTABLE:

STABLE: XXX

CONDITIONS TO AVOID

High humidity, extreme temperatures

INCOMPATIBILITIES (MATERIALS TO AVOID)

Strong reducing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Decomposition will not occur if handled/stored properly. Thermal decomposition may emit toxic substances.

HAZARDOUS POLYMERIZATION MAY OCCUR:

WILL NOT OCCUR: XXX

CONDITIONS TO AVOID

None known

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.